



Toll Free: 866-822-7758 Fax: 610-430-3588

GPT

Automotive Lead-Free Polyvinylchloride (PVC) Wire SAE J-1128 (-40C to 105C)

Lubker Distribution P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	Standard Drum 22", 30"	Standard Reel 12" / 16"
GPT22	22	7/30 Bare	.023	.077	4	30M', N/A	5M'
GPT20	20	7/28 Bare	.023	.084	6	25M', 40M'	5M'
GPT18	18	16/30 Bare	.023	.092	8	25M', 40M'	5M'
GPT16	16	19/29 Bare	.023	.103	11	15M', 30M'	5M'
GPT14	14	19/27 Bare	.023	.117	16	10M', 20M'	5M'
GPT12	12	19/25 Bare	.026	.142	24	10M', 15M'	3M'
GPT10	10	19/23 Bare	.031	.177	41	6M', 10M'	2.5M'
GPT8	8	19/21 Bare	.037	.222	61	3M', 5M'	1.5M'

- Can be used in automotive applications for general circuit wiring and automotive or marine applications where 105C is required.
- Meets Ford ESB-M1L 56A 80C, Ford ESB-M1L 58A 105C, and Chrysler MS-3450 specifications.
- GPT22 meets Ford ESB-M1L 56A only because Ford ESB-M1L 58A requires .010 insulation instead of normal .023.
- We can stripe, print, respool, or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Dark green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Dark blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	