



Toll Free: 866-822-7758 Fax: 610-430-3588

## Trailer Cable - TPE (-70C TO 105C)

Lubker Distribution P/N	AWG Size	NO. of Conds.	Conductor Colors	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.
TRC1604TPE	16	4	blk, wht, brn, red	19/29 Bare	.023	.030	.350	120
TRC1604TPE1	16	4	red, grn, brn, yel	19/29 Bare	.023	.030	.350	120
TRC1606TPE	16	6	blk, wht, brn, grn, red, yel	19/29 Bare	.023	.030	.370	150
TRC1404TPE	14	4	blk, wht, brn, red	19/27 Bare	.023	.045	.420	150
TRC1404TPE1	14	4	red, grn, brn, yel	19/27 Bare	.023	.045	.420	150
TRC1406TPE	14	6	blk, wht, brn, grn, red, yel	19/27 Bare	.023	.060	.490	150
TRC1407TPE	14	7	blk, wht, brn, grn, red, yel, blu	19/27 Bare	.023	.060	.520	150
TRC14/4-12/1-10/2TPE	14	4	brn, yel, grn, red	19/27 Bare	.023	.070	.600	150
	12	1	blu	19/25 Bare	.026			
	10	2	blk, wht	19/23 Bare	.031			
TRC1204TPE	12	4	blk, wht, brn, red	19/25 Bare	.026	.070	.470	250
TRC1206TPE	12	6	blk, wht, brn, grn, red, yel	19/25 Bare	.026	.070	.495	320
TRC12/6-10/1TPE	12	6	blu, brn, grn, red, yel, blk	19/25 Bare	.026	.070	.600	350
	10	1	wht	19/23 Bare	.031			
TRC12/4-10/2-8/1TPE	12	4	yel, blk, brn, grn	19/25 Bare	.026	.070	.680	420
	10	2	blu, red	19/23 Bare	.031			
	8	1	wht	19/21 Bare	.037			
<b>Blue Trailer Cable</b>								
TRC1404BLUTPE2	14	4	yel, brn, grn, wht	19/27 Bare	.023	.045	.420	150
TRC1406BLUTPE	14	6	blk, wht, brn, grn, red, yel	19/27 Bare	.023	.060	.490	150
TRC12/6-10/1BLUTPE	12	6	blu, brn, grn, red, yel, blk	19/25 Bare	.026	.070	.600	350
	10	1	wht	19/23 Bare	.031			

- Normal color code is red, white, black, brown, green, yellow, blue.
- Can be used for automotive trailers, trucks or applications with good resistance to weather, oil and grease.
- Trailer cable inner conductors are stranded copper and color coded for identification purposes with a Thermoplastic Elastomer (TPE) jacket.
- Stranding, insulation thickness, jacket thickness and color code can vary.
- Trailer cable specifications can vary. Please contact your salesperson for any constructions not shown.