



Toll Free: 866-822-7758 Fax: 610-430-3588

Brake Cable

Flat Jacketed Polyvinylchloride (PVC) Automotive Brake Cable (105C)

Lubker Distribution P/N	AWG Size	NO. of Conductors	Conductor Stranding	Wall Thickness	Nominal O.D.	Approx. Lbs./Mft.
BRC1802GRY	18	2	16/30 Bare	.023	.150 X .240	33
BRC1602GRY	16	2	19/29 Bare	.023	.162 X .265	36
BRC1603GRY	16	3	19/29 Bare	.023	.162 X .365	66
BRC1604GRY	16	4	19/29 Bare	.023	.195 X .510	77
BRC1402GRY	14	2	19/27 Bare	.023	.180 X .300	40
BRC1403GRY	14	3	19/27 Bare	.023	.180 X .420	75
BRC1404GRY	14	4	19/27 Bare	.023	.210 X .560	92
BRC1202GRY	12	2	19/25 Bare	.026	.210 X .360	71
BRC1203GRY	12	3	19/25 Bare	.026	.210 X .500	99
BRC1204GRY	12	4	19/25 Bare	.026	.240 X .665	140
BRC1002GRY	10	2	19/23 Bare	.031	.235 X .420	113
BRC1003GRY	10	3	19/23 Bare	.031	.235 X .595	144
BRC1004GRY	10	4	19/23 Bare	.031	.250 X .775	185
BRC0802GRY	8	2	19/21 Bare	.037	.290 X .520	180

- Can be used in electric brake, and many automotive, truck or trailer applications.
- Normal 2 cond color code is black, white.
- Normal 3 cond color code is black, green, white.
- Normal 4 cond color code is black, red, green, white.
- Consult your sales person for availability of other color codes and jacket colors.
- Buy standard put-ups for quicker delivery. Respooling and coiling available.