



Toll Free: 866-822-7758 Fax: 610-430-3588

SEOOW Portable Service Cord

(-50C to 105C) (600 Volts)

Non-UL Listed/Non-CSA Certified

Lubker Distribution P/N	AWG Size	NO. of Cond.	Conductor Stranding	Nominal Insulation	Jacket Thickness	Nominal Diameter	Approx. Lbs./Mft.	Ampacity NEC*
SEO0803	8	3	96/28	.048	.090	.700	332	40
SEO0804	8	4	96/28	.048	.100	.783	425	35
SEO0805	8	5	96/28	.048	.100	.850	509	28
SEO0602	6	2	96/26	.048	.090	.752	332	55
SEO0603	6	3	96/26	.048	.100	.818	473	55
SEO0604	6	4	96/26	.048	.100	.892	594	45
SEO0403	4	3	96/24	.048	.110	.982	677	70
SEO0404	4	4	96/24	.048	.125	1.104	886	60
SEO0203	2	3	7x17/23	.050	.128	1.158	1024	95
SEO0204	2	4	7x17/23	.050	.125	1.267	1350	80

*Per table 400-5(B) of the NEC

- Can be used indoors and outdoors for garages, portable lights, battery charges, portable stage lights, heavy tools and equipment exposed to oils, water, acids, chemicals and solvents. Flame retardant with outstanding abrasion resistance.
- Stocked with black outer jacket.
- Conductor code: 2 conductor is black, white; 3 conductor is black, white, green; 4 conductor is black, white, green, red; 5 conductor is black, white, red, green, orange.
- Portable control cable of 5 conductors or more is also available.
- MSHA, Pennsylvania DEP approved, and Federal spec JC580B.