



Toll Free: 866-822-7758 Fax: 610-430-3588

Trailer Cable - PVC (-50C to 80C)

Lubker Distribution P/N	AWG Size	NO. of Cond.	Cond. Colors	Conductor Stranding	Nom. Insul.	Jacket Thickness	Nom. Diam.	Approx Lbs./Mft.
TRC1604BLK	16	4	blk, wht, brn, red	19/29 Bare	.023	.030	.375	120
TRC1604BLK1	16	4	red, grn, brn, yel	19/29 Bare	.023	.030	.375	120
TRC1606BLK	16	6	blk, wht, brn, gm, red, yel	19/29 Bare	.023	.030	.440	150
TRC1606BLK1	16	6	blk, red, brn, gm, blu, yel	19/29 Bare	.023	.030	.440	150
TRC1404BLK	14	4	blk, wht, brn, red	19/27 Bare	.023	.045	.420	150
TRC1404BLK1	14	4	red, grn, brn, yel	19/27 Bare	.023	.045	.420	150
TRC1406BLK	14	6	blk, wht, brn, gm, red, yel	19/27 Bare	.023	.060	.490	190
TRC1406BLK1	14	6	blk, red, brn, gm, blu, yel	19/27 Bare	.023	.060	.490	190
TRC1407BLK	14	7	blk, wht, brn, gm,	19/27 Bare	.023	.060	.535	220
TRC14/4-12/1-10/2BLK	14	4	brn, yel, grn, red	19/27 Bare	.023	.070	.560	270
	12	1	blu	19/25 Bare	.026			
	10	2	blk, wht	19/23 Bare	.031			
TRC1204BLK	12	4	blk, wht, brn, red	19/25 Bare	.026	.070	.510	250
TRC1206BLK	12	6	blk, wht, brn, gm, red, yel	19/25 Bare	.026	.070	.560	320
TRC12/6-10/1BLK	12	6	blu, brn, gm, red, yel, blk	19/25 Bare	.026	.070	.600	350
	10	1	wht	19/23 Bare	.031			
TRC12/4-10/2-8/1GRN	12	4	yel, blk, brn, gm	65/30 Bare	.026	.070	.710	420
	10	2	blu, red	105/30 Bare	.031			
	8	1	wht	168/30 Bare	.037			

- P/N TRC12/4-10/2-8/1 is normally stocked with a green PVC jacket. SAE also approves this cable as ABS compliant due to the flexible stranding and the presence of two 10 AWG conductors.
- Can be used for automotive trailers, trucks or applications with good resistance to weather, oil and grease
- Trailer cable inner conductors are stranded copper and color-coded for identification purposes with a PVC jacket.
- TPE can be substituted for PVC in extremely low temperature applications.
- Trailer cable specifications can vary. Please contact your salesperson for any constructions not shown.