



Toll Free: 866-822-7758 Fax: 610-430-3588

Welding Cable

Ethylene-propylene-diene monomer (EPDM) Class K (30 AWG) (-50 to 105C) (600V)

Lubker Distribution P/N	AWG Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.
WC6	6	266/30 Bare	0.06	0.320	116
WC4	4	392/30 Bare	0.06	0.375	163
WC3	3	525/30 Bare	0.06	0.428	215
WC2	2	644/30 Bare	0.06	0.440	252
WC1	1	784/30 Bare	0.08	0.515	321
WC1/0	1/0	1026/30 Bare	0.08	0.550	389
WC2/0	2/0	1254/30 Bare	0.08	0.590	474
WC3/0	3/0	1615/30 Bare	0.08	0.660	601
WC4/0	4/0	2052/30 Bare	0.08	0.725	763
WC250	250	2451/30 Bare	0.125	0.875	1029
WC350	350	3458/30 Bare	0.125	0.998	1372
WC500	500	4921/30 Bare	0.125	1.150	1882

- Can be used for welding equipment, portable lighting, automotive starters or battery ground.
- High tear strength jacket with excellent resistance to abrasion and impact.
- Oil and solvent resistant.
- Superior low temp flexibility with good flame resistance.
- Weather, ozone and sunlight resistant jacket.
- Buy standard put-ups for quicker delivery. Respooling and coiling available.
- All sizes stocked in black. 6AWG to 4/0 also stocked in red.