



Flat Head

METRIC

Self - Tapping Screws



METRIC - PHILLIPS FLAT HEADS FOR SELF-TAPPING SCREWS

ISO 7050

Nominal Diameter	Thread Pitch	A	H		K	M	G		Phillips Driver Size	
		Distance from underside of head to 1st major diam of thread	Head Diameter		Head Height	Recess Diameter	Recess Penetration			
		Max	Max	Min	Max	Ref	Max	Min		
ST 2.2	0.8	0.8	3.8	3.5	1.1	1.9	1.2	0.9	0	
ST 2.9	1.1	1.1	5.5	5.2	1.7	3.2	2.1	1.7	1	
ST 3.5	1.3	1.3	7.3	6.9	2.35	4.4	2.4	1.9	2	
ST 4.2	1.4	1.4	8.4	8	2.6	4.6	2.6	2.1	2	
ST 4.8	1.6	1.6	9.3	8.9	2.8	5.2	3.2	2.7	2	
ST 5.5	1.8	1.8	10.3	9.9	3	6.6	3.3	2.8	3	
ST 6.3	1.8	1.8	11.3	10.9	3.15	6.8	3.5	3	3	
ST 8	2.1	2.1	15.8	15.4	4.65	8.9	4.6	4	4	
ST 9.5	2.1	2.1	18.3	17.8	5.25	10	5.7	5.1	4	

METRIC - SLOTTED FLAT HEADS FOR SELF-TAPPING SCREWS

ISO 1482

Nominal Diameter	Thread Pitch	A	H		K	N		T	
		Distance from underside of head to 1st major diam of thread	Head Diameter		Head Height	Slot Width		Slot Depth	
		Max	Max	Min	Max	Max	Min	Max	Min
ST 2.2	0.8	0.8	4.4	3.8	1.1	0.7	0.56	0.6	0.4
ST 2.9	1.1	1.1	6.3	5.5	1.7	1	0.86	0.85	0.6
ST 3.5	1.3	1.3	8.2	7.3	2.35	1.2	1.06	1.2	0.9
ST 4.2	1.4	1.4	9.4	8.4	2.6	1.51	1.26	1.3	1
ST 4.8	1.6	1.6	10.4	9.3	2.8	1.51	1.26	1.4	1.1
ST 5.5	1.8	1.8	11.5	10.3	3	1.91	1.66	1.5	1.1
ST 6.3	1.8	1.8	12.6	11.3	3.15	1.91	1.66	1.6	1.2
ST 8	2.1	2.1	17.3	15.8	4.65	2.31	2.06	2.3	1.8
ST 9.5	2.1	2.1	20	18.3	5.25	2.81	2.56	2.6	2