



TORX® DRIVE PAN HEADS								Camcar
Screw Size	D		H		R	G	Driver Size	
	Head Dimensions				Recess Dimensions			
	Head Diameter		Head Height		Ref	Gauge Penetration Min		(Fallaway) Max Penetration
	Max	Min	Max	Min				
2	.167	.155	.062	.053	.094	.030	.019	T8
4	.219	.205	.080	.070	.111	.035	.022	T10
6	.270	.256	.097	.087	.132	.045	.026	T15
8	.322	.306	.115	.105	.155	.055	.031	T20
10	.373	.357	.133	.122	.178	.070	.036	T25
12	.425	.407	.151	.139	.200	.070	.040	T27
1/4	.492	.473	.175	.162	.221	.085	.044	T30
5/16	.615	.594	.218	.203	.266	.105	.047	T40



PHILLIPS AND SLOTTED COMBINATION DRIVE PAN HEADS																
Nominal Screw Size	G		H		J		A		M		T		N	Recess Penetration Gaging Depth		Driver Size
	Head Dimensions				Slot Dimensions				Recess Dimensions							
	Head Diameter		Head Height		Width		Depth		Diameter		Depth		Width	Max	Min	
	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Ref			
4	.219	.205	.080	.070	.039	.031	.040	.030	.122	.109	.078	.060	.019	.071	.053	1
6	.270	.256	.097	.087	.048	.039	.050	.037	.166	.153	.091	.066	.028	.080	.055	2
7	.296	.281	.106	.096	.048	.039	.054	.041	.176	.163	.100	.074	.029	.089	.064	2
8	.322	.306	.115	.105	.054	.045	.058	.045	.182	.169	.108	.082	.030	.097	.071	2
10	.373	.357	.133	.122	.060	.050	.068	.053	.199	.186	.124	.100	.031	.113	.089	2
12	.425	.407	.151	.139	.067	.056	.077	.061	.259	.246	.141	.115	.034	.124	.098	3
1/4	.492	.473	.175	.162	.075	.064	.087	.070	.281	.268	.161	.135	.036	.144	.118	3