



COUNTERSUNK EXTERNAL TOOTH LOCKWASHERS								ASME B18.21.1-1999
Nominal Washer Size		A		B	C		D	
		Inside Diameter		Outside Diameter	Thickness		Length	
		Max	Min	Approx	Max	Min	Max	Min
4	0.112	0.123	0.113	0.213	0.019	0.015	0.065	0.050
6	0.138	0.150	0.140	0.289	0.021	0.017	0.092	0.082
8	0.164	0.177	0.167	0.322	0.021	0.017	0.099	0.083
10	0.190	0.205	0.195	0.354	0.025	0.020	0.105	0.088
12	0.216	0.231	0.220	0.421	0.025	0.020	0.128	0.118
1/4	0.250	0.267	0.255	0.454	0.025	0.020	0.128	0.113
5/16	0.3125	0.333	0.318	0.599	0.028	0.023	0.192	0.165
3/8	0.375	0.398	0.383	0.765	0.034	0.028	0.255	0.242
1/2	0.500	0.529	0.512	0.976	0.045	0.037	0.304	0.294

Description	An external tooth lock washer with a conical shaped bearing surface.
Applications/ Advantages	Designed for use with flat or oval head screws with countersunk angles of 82° or 100°.
Material	SAE 1050 - 1065 or equivalent spring steel
Hardness	Rockwell C40 - 50
Plating	See Appendix-A for information on the plating of steel lock washers.